



LUXOL XTRA

SUPER GLOSS ENAMEL



Product Attributes



Mirror-like finish

It gives superior mirror-like gloss for doors, windows, grills and masonry surfaces making them look good for years

Tough Film & Durability
It has an oil-based protective covering that acts as a shield for your doors, windows, grills etc.

The tough solvent-based coating is suitable for Indian weather conditions, providing sustainable cover



Superior Coverage

Gives a superior coverage over other high gloss enamels

Green Pro Certified

Validates our effort in striving towards cleaner, more sustainable future



Product Description

Berger Luxol XTRA Super Gloss Enamel is manufactured with suitable alkyd, finest pigments and few important additives. It offers a superior mirror-like gloss with tough film and an everlasting finish, that can be used both for exterior and interior surfaces, such as mild steel, wood and suitably prepared masonry surfaces.

Recommended Use

Mild steel, wood, and prepared masonry surfaces.

Recommended Primers

- Wall/ Plastered surfaces – BP Cement Primer (ST)
- Metal surfaces - Butterfly A/C Metal Primer, Luxol Zinc Chromate Primer
- Wooden surfaces – Parrot Wood Primer

Colour Range



Over 2000 shades

Finish

VERY HIGH

HIGH

SOFT SHEEN ✓

MATT

Soft sheen finish

Toxicity



NA

Coverage



Brush application - approx. 95-125 sq.ft./L/2 coats, under ideal test conditions

(Coverage may depend on factors like surface conditions, surface preparation, application skill, weather conditions, dilution etc.)

Drying Time



SD: 2 -3hrs depending on weather conditions

Recommended Dilution



10 - 15% (v/v)

Application Method



Brush, Roller & Spray

Recommended Thinner



Thinner 800

Flash Point



Not below 37° C

Sheen Level



20 ± 5 at 60° on glass plate when released

Viscosity



Brushing - 40 - 45 sec at 30°C
Spraying - 25 - 30 sec at 30°C
Roller - 60 - 65 sec at 30°C



LUXOL XTRA

SUPER GLOSS ENAMEL



Packs



10L



20 L

Non ColorBank
10L, 20L

ColorBank
450ml, 495ml, 900ml, 950ml,
985ml, 3.6L, 3.8L, 3.9L, 18L, 19L Bases

Bases (ColorBank)
W1, W2, W3, P0, N, Dark Brown, Light
Brown, Blue, Bright Yellow

Offered Shade Range
Over 2000 shades



Fire Hazard Class
Flammable



Pot Life of Thinned Material
Within 24hrs

Shelf Life
1 year

Surface Preparation

For Cement plaster/ Wood /Metal surface:



Initially sand the surface with coarse Sandpaper / Water paper according to the type of surface to be prepared. Remove rust, dust and other loose unwanted particles. Wipe the surface clean.

Application Process

Primer Application:



Apply 1st coat of primer after proper dilution and allow it to dry fully



Sand the surface again with less coarser Water paper and wipe clean. Again apply 2 coats of primer giving overnight interval between coats. Sand it again with Water paper No.220/280

For Wooden & Metal surface: Apply 1st coat of Luxol Speed Coat Primer Surfacer with proper dilution.

For Wall surface: Apply 1 coat of solvent-based Cement Primer with ideal dilution.

Allow the surfaces to dry dully. Then sand the primed surface with Water Paper No. 380/400 lightly to make the surface smooth and undulation free.

Application of Topcoat:

Before the application of topcoat, first sand the surface lightly with Water paper No. 400/600. Ensure the surface pH is within 7-11.

Then dilute the paint and strain it through a clean cloth. Apply 2 - 3 coats of LuxolXtra Super Gloss Enamel to get rich, smooth and silky finish. Give overnight drying interval between coats.

Special Note

Use only toilet soap to clean stains

Before painting the following things should be checked thoroughly:

1. Moisture content of the wall (ideal condition - below 12%)
2. pH value of the wall surface (ideal condition - between 7 -11)

Points to Note

- ▶ Shake well before use and do not over dilute
- ▶ Strain the material through a fine sieve before use
- ▶ Keep the container tightly closed to prevent drying
- ▶ Use 1-2 coats of Bio - Wash for killing fungal growth
- ▶ Keep out of reach of children and away from foodstuff
- ▶ In case of contact with eyes, wash immediately with water and seek medical help
- ▶ For deeper shade apply 1 additional coat

Version No: BPP1/11/2014. Please note that this data sheet supersedes all previous versions.

BERGER PAINTS INDIA LIMITED

Berger House, 129 Park Street, Kolkata 700 017 | **CONSUMER RELATIONS MANAGER** Ph: 1800-103-6030
Fax: 91-33-2249-9729/9009 | SMS BERGER to 56767 | Email: consumerfeedback@bergerindia.com | www.bergerpaints.com